

### Product Data Sheet

SAMBA Code: 695



#### General

|               |                         |
|---------------|-------------------------|
| Enertec Code: | 21BAT695-BLC            |
| Technology:   | Sealed Flooded Battery  |
| Alloy:        | Silver/Calcium          |
| Maintenance:  | Sealed Maintenance Free |
| Short Code:   | 695-BLC                 |
| Charge Eye:   | Yes                     |

#### Electrical Specifications


|                    |        |
|--------------------|--------|
| Voltage:           | 12 V   |
| Capacity (20 hrs): | 200 AH |
| CCA SAE (- 18°C):  | 1200   |

#### Transportation

|                                                      |              |
|------------------------------------------------------|--------------|
| Classified as:                                       | Lead Acid    |
| Batteries, wet, filled with acid, electrical storage |              |
| UN number:                                           | UN 2794      |
| Classification (ADR/RID)                             | Class 8      |
| Packing Group                                        | Not Assigned |

#### Dimensions / Mass

|                    |         |
|--------------------|---------|
| Max Length (L):    | 516 mm  |
| Max Width (W):     | 275 mm  |
| Max Height (H):    | 217 mm  |
| Total Height (TH): | 242 mm  |
| Mass (Weight):     | 51.5 kg |



#### Container

|                   |               |
|-------------------|---------------|
| Group Size:       | Typ C / N200  |
| Case Material:    | Polypropylene |
| Colour:           | Grey / Blue   |
| Bottom Hold Down: | B00           |
| Terminal Type:    | Tapered (1)   |
| Layout:           | LHP (3)       |

#### Terminal



01


#### Layout



#### Hold-down




B00



PUNCHED  
GRID

**OE**

MATCHING  
QUALITY



VIBRATION  
RESISTANT



HIGH  
HEAT



SILVER (Ag)  
CALCIUM (Ca)