

Product Data Sheet

SAMBA Code: 643




General	
Enertec Code:	20BAT643-BLC
Technology:	Sealed Flooded Battery
Alloy:	Silver/Calcium
Maintenance:	Sealed Maintenance Free
Short Code:	643-BLC
Charge Eye:	Yes


Electrical Specifications	
Voltage:	12 V
Capacity (20 hrs):	55 AH
CCA SAE (- 18°C):	550


Transportation	
Classified as:	Lead Acid
Batteries, wet, filled with acid, electrical storage	
UN number:	UN 2794
Classification (ADR/RID)	Class 8
Packing Group	Not Assigned

Dimensions / Mass	
Max Length (L):	242 mm
Max Width (W):	175 mm
Max Height (H):	190 mm
Total Height (TH):	190 mm
Mass (Weight):	13.8 kg



Container	
Group Size:	L2R
Case Material:	Polypropylene
Colour:	Grey / Blue
Bottom Hold Down:	B13
Terminal Type:	Tapered (1)
Layout:	LHP (1)


Terminal	Layout	Hold-down
 01		 B13



PUNCHED
GRID



MATCHING
QUALITY



VIBRATION
RESISTANT



HIGH
HEAT



SILVER (Ag)
CALCIUM (Ca)