Encube Series VC12100 Plus

12V LiFePO4 Li-ion Battery



Cell Balancing, Extend lifetime of battery.Current >300mA

Safeandreliable ThesafestLFPbatterycell Bluetooth built-in Easy to access battery status

Battery management system with chip

Supports series and parallel use

High compatibility Support to connect with lead-acid battery

Application Scenario















Electrical

Nominal Voltage/V	12.8
Nominal Capacity/Ah	100
Rated Energy/Wh	1280
BMS Function	Overcharge, overdischarge, overcurrent and temperature protection
Recommended Charge Voltage/V	14.4 - 14.6
Discharge Cut-off Voltage/V	10.8
Standard Charge Current/A Max.	50
Charge Current/A Continuous	100
Discharge Current/A Peak	100
Discharge Current/A@5S	300
Voltage Configurations	12,24,36 or 48V
Maximum Configuration	Max 4 units in series and parallel
Maximum Time Between Charges	3 months
Monitoring	Bluetooth

Mechanical

Dimension(L*W*H)/ mm	307*169*213
Weight/kg	Approx.11.5
Terminal	M8
Casing material	ABS

Environment

Working Temperature Range/°C	Charge: 0~55 Discharge: -20~60
Humidity Range/RH	<95%
Storage temperature/°C	15~35
IP protection level	IP65





